

Congratulations on your new balcony glazing!

Now you can finally enjoy your balcony all year round, regardless of the weather. We at Alnova are delighted to be a part of your home upgrade and are always here if you have any questions or need our help.

Take advantage of our tips for making the most out of your glazed balcony:

- The glazing system provides good protection against wind and water, but there's no guarantee the balcony will be entirely draft-free or waterproof. The glazing is designed to drain away incoming water. During windy and rainy weather, these drainage holes can leak water, which will be discharged after the rainy weather stops, depending on the slope of the balcony tiles. Consider this when choosing furniture and equipment for your balcony.
- Our frameless enclosures have an air gap between the glasses of approximately 2-4 mm. If you desire a slightly tighter seal, you can purchase optional plastic sealing strips and install them yourself. Regardless of the model or brand you choose for your glazing, some noise may occur during moderate to strong winds.
- Consider fire safety and child safety when furnishing your balcony. Avoid placing too much fixed furniture on the balcony.
- If you wish to have sun protection for your balcony glazing, Alnova offer customized blinds as an option.
- When using flower boxes on the balcony, these should, in consultation with the property owner or manager, be installed on the inside of the glazing. In cases where the box is attached to the railing, choose a box made of rubber-coated aluminum or plastic.
- Many facades have joints and gaps where water can seep in, and during rain and wind, water may sometimes leak onto the balcony. This is not a fault in the glazing and must be solved in another way, such as through sealing or tinning. To solve the issue, you should first contact the property company that owns and/or manages the building or the construction company.
- Rainwater may sometimes contain a high pH-value due to building materials, such as balcony tiles, which can cause marks on the glass that cannot be washed away. Drip tray is an option that can divert water a bit outside the railing and glazing

If you have questions or want to purchase additional balcony add-ons such as sealing strips, drip trays, or blinds, don't hesitate to contact us at Alnova Balkongsystem +46 10-16 13 400



VingaLine Skjutsystem

Manage your glazing

VingaLine with sliding doors and panels is a glazing system installed inside existing balcony railings. Doors and windows slide along track profiles thanks to high-quality nylon wheels. The glasses can be slid both to the right and left but cannot pass each other. The locking mechanism is integrated into the handle as a snap function.

Opening and closing

1. The child lock is a metal knob positioned approximately 1.8 meters above the floor. To open the lock, pull the knob towards you and turn it 1/4 turn to the unlocked position.
2. Grip the handle of the door or panel and squeeze while pushing it to the side.
3. To close, pull the door or panel toward the side strip, which has a built-in hook, so the handle snaps onto the strip. Remember to lock the child lock by turning it back 1/4 turn.

Attention! To prevent damage to the glazing system, keep the glazing system closed in moderate and stronger wind conditions.

Cleaning (fold-in)

The glass panels can be folded 90° inward towards the balcony to facilitate cleaning of the outside of the glass. When cleaning the outside of the glass, the panel is removed from the system. When placing back the panel, it's important to ensure it aligns correctly in the track to avoid jamming of the sliding function, and in the worst case, the panel falling out.

Note! The fold-in function is not intended for ventilation, only for cleaning the glass!

Cleaning the outside of the glass:

1. Free the frame of the panel.
2. Use a screwdriver or similar tool to turn the two locks on each sliding panel counterclockwise, and the glass will detach.
3. Fold out the glass, but avoid opening the inner window more than 90° in relation to the outer frame. Also, avoid putting weight on the glass or "hanging" on the top. It's advisable to support the inner window during cleaning.

Closing the window panels after cleaning:

4. Due to the weight of the glass, it might slightly hang in relation to the outer frame. Therefore, gently lift the bottom edge of the glass to facilitate closing. The glass should slide on the black plastic strip at the bottom.
5. Ensure the glass is completely closed. Then, turn both locks clockwise until they are properly engaged.